

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Component housing without vents, Lower part, Cross connection: DIN rail bus connector, Color: light gray, Width: 35 mm, Constructional height: 114.5 mm, Number of positions cross connector: 5

Why buy this product

- ▼ Tool-free mounting
- Available in overall widths from 12.5 mm to 90 mm, modular extension is possible
- ✓ Inflammability class V0 according to UL 94
- Variety of connection technologies
- Can be mounted on the DIN rail
- Optional bus connector that is either integrated or mounted on the DIN rail



Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
Weight per Piece (excluding packing)	59.790 g
Custom tariff number	85472000
Country of origin	Germany

Technical data

Environmental Product Compliance

China RoHS	No hazardous substances above threshold values
General	
Housing type	Component housing
Housing material	Polyamide
Color	light gray



Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)
D'accestication	

Dimensions

Length	99 mm
Constructional height	114.5 mm
Width	35 mm

Technical data

Flammability rating according to UL 94	V0
Power dissipation without gap	7.5 W
Power dissipation with 20 mm gap	13.8 W
Number of positions	24

Standards and Regulations

	
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC001031

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501



Classifications

UNSPSC

UNSPSC 13.2	31261501	
Approvals		
Approvals		

Approvals

UL Recognized

Ex Approvals

Approval details

UL Recognized 1 http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 240868

Accessories

Accessories

Mounting material

Electronic housing - ME LPZS - 2906911



Component housing

Necessary add-on products

Electronic housing - ME 35 OT-MSTBO KMGY - 2914864



Component housing, Upper part, Color: light gray, Width: 35 mm, Constructional height: 38.5 mm



Accessories

Electronic housing - ME 17,5 OT-FKDSO KMGY - 2200322



Component housing, Upper part, Color: light gray, Width: 17.5 mm, Constructional height: 38.5 mm

Electronic housing - ME 17,5 OT-MSTBO KMGY - 2853747



Component housing, Upper part, Color: light gray, Width: 17.5 mm, Constructional height: 38.5 mm

Electronic housing - ME 17,5 OTU-MKDSO KMGY - 2278940



Component housing, Upper part, Color: light gray, Width: 17.5 mm, Constructional height: 38.5 mm

Electronic housing - ME 17,5 OTP-MSTBO PS KMGY - 2279253



Component housing, Upper part, Color: light gray, Width: 17.5 mm, Constructional height: 38.5 mm

Additional products

Electronic housing - ME 17,5 TBUS 1,5/5-ST-3,81 KMGY - 2713645



Plug component, Nominal current: 8 A, Number of positions: 5, Pitch: 3.81 mm



Accessories

Electronic housing - ME 17,5 TBUS 1,5/4P1S KMGY - 2201731



DIN rail connector for ME and ME-MAX, design width: 17.5 mm, 4 parallel positions and 1 serial position, color: light gray (similar to RAL 7035)

Electronic housing - ME 17,5 TBUS ADAPTER KMGY - 2201757



DIN rail bus adapter for ME and ME-MAX, design width: 17.5 mm, 5 parallel positions, color: light gray (similar to RAL 7035)

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com